

MULTI-SOURCE FLAT PANEL CCTV MONITORS

XP SERIES | XPI7AV

FOR HIGH-END RESIDENTIAL, CORPORATE AND RETAIL INSTALLATIONS



3 year warranty

FEATURES

- 17" TFT LCD
- Composite / VGA / DVI Inputs
- Resolution: SXGA 1280 x 1024
- Contrast Ratio: 500:1 (typical)
- BNC with Loop Through
- Protective Optical Glass Filter
- Rugged Aluminum Alloy Construction
- Security Industry Compatibility
- EVS Input Technology
- Wall or Arm Mount Available



About the NeoV Optical Filter:

The NeoV Optical Filter is a specially formulated, hardened optical glass (6H Moh's Rating) that is built on top of the internal LCD panel to dramatically enhance image quality and protect the screen from damage.



About EVS Input Technology:

Enhanced Video Signal (EVS) Input monitors provide the highest compatibility with CCTV equipment and enhanced video clarity. Unlike many flat panel monitors designed for the PC industry, EVS enabled monitors will not experience dropped signals as a result of video signal hunting. Dropped signals and poor composite video quality have made most flat panel monitors (designed for the PC industry) difficult and undesirable to use with multiplexers and digital recorders. AGNPRO monitors are designed for video surveillance applications and are the most compatible in the industry.

SPECIFICATION

Available in 17", 19" TFT LCD. 15" and 20.1" available in X-Series*

| | | |
|----------------------|---|---|
| Panel | Panel Type Max. Resolution Pixel Pitch Contrast Ratio Brightness Display Colors Response Time Wide Viewing Angle | 17" TFT LCD SXGA 1280 x 1024 0.264mm 500:1 250cd/m2 16.7M 25ms (Total) 170°/170° |
| Inputs | Input Type Video Standard | Composite / VGA / DVI NTSC/PAL/SECAM |
| Connectors | Composite S-Video VGA Digital (DVI-D) | BNC In / Out Loop-through N/A 15-Pin D-Sub 29-Pin DVI |
| EVS Input Technology | Enabled | Yes |
| Protective Glass | NeoV Optical Filter | 6H (Moh's Rating) |
| Special Features | | Aluminum Alloy Construction, Kensington Lock |
| Tilt | Angle | 0°-15° |
| Mounting | Vesa FPMPI | Yes (100mm) |
| Regulation Approval | Safety & EMI | FCC, UL/CUL, TUV / BAURT, CE, NORDIC, TCO '95, BSMI, VCCI, CB, ISO 13406-2 |
| Power | Power Source Consumption | 100 - 245V, 50 - 60Hz <48W (On) <5W (Off) |
| Dimensions | Net (W X H X D) Packing (W X H X D) | 16.1" x 15.7" x 6.9" 19.5" x 20" x 9" |
| Weight | Net Weight Gross Weight | 13.9 lb (6.8Kg) 20.9 lb (9.5Kg) |

All specifications are subject to change without prior notice.

* X-15AV, X-20AV

