

MULTI-SOURCE FLAT PANEL CCTV MONITORS

XP SERIES | XPI9AV

FOR HIGH-END RESIDENTIAL, CORPORATE AND RETAIL INSTALLATIONS



3 year warranty

FEATURES

- 19" TFT LCD
- Composite / VGA / DVI Inputs
- Resolution: SXGA 1280 x 1024
- Contrast Ratio: 700:1 (typical)
- BNC with Loop Through
- Protective Optical Glass Filter
- Rugged Aluminum Alloy Construction
- Security Industry Compatibility
- EVS Input Technology
- Wall or Arm Mount Available



About the NeoV Optical Filter:

The NeoV Optical Filter is a specially formulated, hardened optical glass (6H Moh's Rating) that is built on top of the internal LCD panel to dramatically enhance image quality and protect the screen from damage.



About EVS Input Technology:

Enhanced Video Signal (EVS) Input monitors provide the highest compatibility with CCTV equipment and enhanced video clarity. Unlike many flat panel monitors designed for the PC industry, EVS enabled monitors will not experience dropped signals as a result of video signal hunting. Dropped signals and poor composite video quality have made most flat panel monitors (designed for the PC industry) difficult and undesirable to use with multiplexers and digital recorders. AGNPRO monitors are designed for video surveillance applications and are the most compatible in the industry.

SPECIFICATION

Available in 17", 19" TFT LCD. 15" and 20.1" available in X-Series*

Panel	Panel Type Max. Resolution Pixel Pitch Contrast Ratio Brightness Display Colors Response Time Wide Viewing Angle	19" TFT LCD SXGA 1280 x 1024 0.294mm 700:1 300cd/m ² 16.7M 25ms (Total) 170°/170°
Inputs	Input Type Video Standard	Composite / VGA / DVI NTSC/PAL/SECAM
Connectors	Composite S-Video VGA Digital (DVI-D)	BNC In / Out Loop-through N/A 15-Pin D-Sub 29-Pin DVI
EVS Input Technology	Enabled	Yes
Protective Glass	NeoV Optical Filter	6H (Moh's Rating)
Special Features		Aluminum Alloy Construction, Kensington Lock
Tilt	Angle	0°-15°
Mounting	Vesa FPMPI	Yes (100mm)
Regulation Approval	Safety & EMI	FCC, UL/CUL, TUV / BAURT, CE, TCO '95, BSMI, VCCI, CB, ISO 13406-2
Power	Power Source Consumption	100 - 245V, 50 - 60Hz <48W (On) <5W (Off)
Dimensions	Net (W X H X D) Packing (W X H X D)	17.5" x 16.5" x 6.9" 21.2" x 20.7" x 9"
Weight	Net Weight Gross Weight	17.4 lb (7.9Kg) 23.57 lb (10.7Kg)

All specifications are subject to change without prior notice.

* X-15AV, X-20AV

